

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Husqvarna 2-Stroke Oil HP

of the mixture

Registration number -

Synonyms None.

Product code 587 80 85-01 (0.1L.), 587 80 85-10 (1L.), 587 80 85-11 (1L.), 587 80 85-12 (1L.), 587 80 85-20

(4L.), 587 80 85-30 (20L.), 587 80 85-40 (208L.)

Issue date 23-December-2014

Version number 01
Revision date Supersedes date -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubrication of 2-stroke engine.

Uses advised againstUse in accordance with supplier's recommendations.

1.3. Details of the supplier of the safety data sheet

Manufacturer/SupplierHusqvarna ABAddressDrottninggatan 2Telephone+46 (0)36-14 65 00Contact personAccessory DepartmentE-mailsds.info@husqvarna.se

1.4. Emergency telephone

+1-760-476-3961 (Access code 333721)

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

This preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary

Physical hazards Not classified for physical hazards.

Health hazards Not classified for health hazards.

Environmental hazards Not classified for hazards to the environment.

Specific hazards Direct contact with eyes may cause temporary irritation. May form vapours or oil mists during

mechanical action or at elevated temperatures which may be irritating to respiratory tract. Prolonged exposure to oil mist may cause pulmonary disease such as chronic inflammation. Prolonged and repeated contact with used oil may cause serious skin diseases, such as

dermatitis and skin cancer.

May cause eye irritation on direct contact. Defatting of the skin. Dermatitis. Ingestion may cause

irritation and malaise. In high concentrations, mists/vapors may irritate throat and respiratory

system and cause coughing.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None.

Signal word None.

Hazard statements None.

Precautionary statements

PreventionNot assigned.ResponseNot assigned.StorageNot assigned.

Husqvarna 2-Stroke Oil HP SDS UK

Disposal Not assigned.

Supplemental label information EUH210 - Safety data sheet available on request.

2.3. Other hazardsNot a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name % CAS-No. / EC No. REACH Registration No. INDEX No. Notes

Highly refined mineral oil > 70 -

(DMSO-extract < 3% IP 346)

Classification: DSD: -

CLP: -

Hydrocarbons, C12-C15, n-alkanes, 10 - 20 - - -

isoalkanes, cyclics, < 2% aromatics 920-107-4

Classification: DSD: Xn;R65, R66

CLP: Asp. Tox. 1;H304

Hydrocarbyl amine 1-5 Polymer - -

Classification: DSD: R52/53

CLP: Aquatic Chronic 3;H412

List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008. DSD: Directive 67/548/EEC.

#: This substance has been assigned Community workplace exposure limit(s).

#. This substance has been assigned Community workplace exposure limit(s).

Composition comments

The full text for all R- and H-phrases is displayed in section 16. All concentrations are in percent by

weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Call a physician if symptoms develop or

persist.

Skin contact Wash with soap and water. In case of rashes, wounds or other skin disorders: Seek medical

attention and bring along these instructions. If high pressure injection under the skin occurs,

always seek medical attention.

Eye contact Flush eyes immediately with large amounts of water. Remove any contact lenses and open eyelids

wide apart. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get immediate

medical attention.

4.2. Most important symptoms and effects, both acute and

delayed

May cause eye irritation on direct contact. Defatting of the skin. Dermatitis. Ingestion may cause irritation and malaise. In high concentrations, mists/vapors may irritate throat and respiratory system and cause coughing.

system and cause cougnil

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Symptoms may be delayed. HIGH PRESSURE SKIN INJECTION: Physician must be familiar with local procedures for treatment of this type of wound; incision, irrigation, removal of all necrotic tissue

and open wound dressing.

SECTION 5: Firefighting measures

General fire hazards Heating will generate vapours which may form explosive vapour/air mixtures. Material will float and

can be re-ignited on surface of water.

5.1. Extinguishing media

Suitable extinguishing Foam. Dry powder. Carbon dioxide (CO2). Water fog.

media

Husqvarna 2-Stroke Oil HP SDS UK

923332 Version #: 01 Revision date: - Issue date: 23-December-2014

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

By heating and fire, irritating vapours/gases may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in

the workplace.

Special fire fighting procedures

Move container from fire area if it can be done without risk. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). In case of spills, beware of slippery floors and surfaces. Wear protective clothing as described in section 8 of this safety data sheet.

For emergency responders

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not allow to enter drains, sewers or watercourses. Environmental manager must be informed of all major releases.

6.3. Methods and material for containment and cleaning up

Remove sources of ignition. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Large Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Wash area with soap and water.

Small Spills: Wipe up spilled material and place in a suitable container for disposal. Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas. Avoid inhalation of oil mist and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Do not eat, drink or smoke when using the product. Be aware of potential for surfaces to become slippery. Observe good industrial hygiene practices. "Empty" containers retain product residue (liquid or vapour) and can be dangerous. Do not cut or weld on empty drums unless they are thoroughly cleaned.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from ignition, flame and heat sources. Store in a cool, dry, well-ventilated place. Store away from incompatible materials.

7.3. Specific end use(s)

Lubrication of 2-stroke engine.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits No exposure limits noted for ingredient(s).

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no-effect level (DNEL) Not available.

Predicted no effect concentrations (PNECs)

Not available.

Exposure guidelines Follow standard monitoring procedures.

8.2. Exposure controls

Appropriate engineering

controls

Provide adequate ventilation and minimise the risk of inhalation of vapours and oil mist. Use explosion-proof equipment. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

General information Personal protective equipment should be chosen according to the CEN standards and in

discussion with the supplier of the personal protective equipment.

Eye/face protection Skin protection Wear safety glasses with side shields (or goggles).

Husqvarna 2-Stroke Oil HP SDS UK

23332 Version #: 01 Revision date: - Issue date: 23-December-2014

Wear protective gloves. Nitrile gloves are recommended, but be aware that the liquid may - Hand protection

penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the

glove supplier.

- Other Wear appropriate clothing to prevent repeated or prolonged skin contact.

In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with Respiratory protection

combination filter (type A2/P2) can be used. Wear air-supplied mask in confined areas. Seek

advice from local supervisor.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

> and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using, do not eat, drink or smoke. Launder contaminated clothing before reuse. Private clothes and working clothes should be kept

separately.

Environmental exposure

controls

Environmental manager must be informed of all major spillages.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Brown liquid. **Appearance Physical state** Liquid. **Form** Liquid. Colour Brown.

Odour Organic solvents. **Odour threshold** Not available. pН Not available. Not available. Melting point/freezing point Not available. Initial boiling point and boiling

range

145.0 °C (293.0 °F) (ISO 2592) Flash point

Not available. **Evaporation rate** Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

< 0.01 kPa @ 20°C Vapour pressure Not available. Vapour density Solubility(ies) Negligible.

Partition coefficient Log Kow: >3 (Estimated).

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available.

57.5 mm2/s (40 °C) (ISO 3104) **Viscosity**

Not available. **Explosive properties Oxidizing properties** Not oxidizing.

9.2. Other information

874.00 kg/m3 (ISO 12185) **Density**

SECTION 10: Stability and reactivity

10.1. Reactivity The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions. 10.3. Possibility of hazardous Hazardous polymerisation does not occur.

reactions

Heat, sparks, flames, elevated temperatures. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous By heating and fire, irritating vapours/gases may be formed. Carbon oxides.

decomposition products

10.4. Conditions to avoid

Husqvarna 2-Stroke Oil HP SDS UK

SECTION 11: Toxicological information

Occupational exposure to the substance or mixture may cause adverse effects. **General information**

Information on likely routes of exposure

Inhalation Inhalation of oil mist or vapours formed during heating of the product will irritate the respiratory

system and provoke coughing.

Prolonged or repeated contact may dry skin and cause dermatitis. Skin contact

Direct contact with eyes may cause temporary irritation. Eye contact

Ingestion may cause irritation and malaise. Ingestion may result in vomiting; aspiration (breathing) Ingestion

of vomitus into lungs must be avoided as even small quantities may result in aspiration

pneumonitis.

Symptoms May cause eye irritation on direct contact. Defatting of the skin. Dermatitis. Ingestion may cause

irritation and malaise. In high concentrations, mists/vapors may irritate throat and respiratory

system and cause coughing.

11.1. Information on toxicological effects

May irritate and cause stomach pain, vomiting, diarrhoea and nausea. Human evidence indicates **Acute toxicity**

> that the product has very low acute oral, dermal or inhalation toxicity. However, it can produce severe injury if taken into the lung as a liquid, and there may be profound central nervous system

depression following prolonged exposure to high levels of vapour.

Skin corrosion/irritation

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

Not classified.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

single exposure

High concentrations: May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Not classified, however droplets of the product may be aspirated into the lungs through ingestion

or vomiting and may cause a serious chemical pneumonia.

Mixture versus substance

information

Not available.

Other information

Prolonged and repeated contact with used oil may cause serious skin diseases, such as

dermatitis and skin cancer.

SECTION 12: Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the 12.1. Toxicity

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.2. Persistence and

degradability

Expected to biodegrade slowly.

12.3. Bioaccumulative potential

The product contains potentially bioaccumulating substances.

Partition coefficient

n-octanol/water (log Kow)

Log Kow: >3 (Estimated).

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil

12.5. Results of PBT

Not available.

Not a PBT or vPvB substance or mixture.

and vPvB assessment

Oil spills are generally hazardous to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

12.6. Other adverse effects

Dispose of in accordance with local regulations. Empty containers or liners may retain some Residual waste

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Husqvarna 2-Stroke Oil HP SDS UK 5/7

SECTION 14: Transport information

ADR

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

ADN

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Code

Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Not listed.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding

Not listed.

Other EU regulations

Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances

Not listed.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Directive 94/33/EC on the protection of young people at work

Not listed.

Husqvarna 2-Stroke Oil HP SDS UK

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws.

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations

15.2. Chemical safety assessment

Follow national regulation for work with chemical agents. No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

References

DNEL: Derived No-Effect Level.

PNEC: Predicted No-Effect Concentration.
PBT: Persistent, bioaccumulative and toxic.
vPvB: Very Persistent and very Bioaccumulative.

HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS) ESIS (European chemical Substances Information System)

Information on evaluation method leading to the classification of mixture

The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if

available. For details, refer to Sections 9, 11 and 12.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

Training information

Follow training instructions when handling this material.

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

Husqvarna 2-Stroke Oil HP SDS UK