

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : SOLID POWER (914100)

Other means of identification : Not applicable

Recommended use : Machine Warewashing Detergent

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : 0.08 % - 0.2 %

Company : Ecolab Inc.  
370 N. Wabasha Street  
St. Paul, Minnesota USA 55102  
1-800-352-5326

Emergency telephone : 1-800-328-0026 (US/Canada), 1-651-222-5352 (outside US)

Issuing date : 01/21/2015

**SECTION 2. HAZARDS IDENTIFICATION**
**GHS Classification**
**Product AS SOLD**

Skin corrosion : Category 1A  
Serious eye damage : Category 1

**Product AT USE DILUTION**

Skin corrosion : Category 1A  
Serious eye damage : Category 1

**GHS Label element**
**Product AS SOLD**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Causes severe skin burns and eye damage.

Precautionary Statements : **Prevention:**  
Wash skin thoroughly after handling.  
**Response:**  
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. Wash contaminated clothing before reuse.  
**Storage:**  
Store locked up.

# SAFETY DATA SHEET

## SOLID POWER (914100)

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Product AT USE DILUTION**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Causes severe skin burns and eye damage.

Precautionary Statements : **Prevention:**

Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. Wash contaminated clothing before reuse.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

Other hazards : None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Product AS SOLD**

Pure substance/mixture : Mixture

Chemical Name	CAS-No.	Concentration (%)
sodium hydroxide	1310-73-2	60 - 100
Sodium Carbonate(soda)	497-19-8	10 - 30
oxirane, methyl-, polymer with oxirane	9003-11-6	1 - 5

**Product AT USE DILUTION**

No hazardous ingredients

### SECTION 4. FIRST AID MEASURES

**Product AS SOLD**

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give

## SAFETY DATA SHEET

### SOLID POWER (914100)

- anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Treat symptomatically.
- Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

#### Product AT USE DILUTION

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

### SECTION 5. FIRE-FIGHTING MEASURES

#### Product AS SOLD

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Not flammable or combustible.
- Hazardous combustion products : Decomposition products may include the following materials:  
Carbon oxides  
Nitrogen oxides (NOx)  
Sulfur oxides  
Oxides of phosphorus
- Special protective equipment for fire-fighters : Use personal protective equipment.
- Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

# SAFETY DATA SHEET

## SOLID POWER (914100)

### Product AS SOLD

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Sweep up and shovel into suitable containers for disposal.

### Product AT USE DILUTION

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

## SECTION 7. HANDLING AND STORAGE

### Product AS SOLD

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Store in suitable labeled containers.

Storage temperature : -10 °C to 50 °C

### Product AT USE DILUTION

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage : Keep out of reach of children. Store in suitable labeled containers.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Product AS SOLD

#### Ingredients with workplace control parameters

Ingredients	CAS-No.	Form of exposure	Permissible concentration	Basis
sodium hydroxide	1310-73-2	Ceiling	2 mg/m <sup>3</sup>	ACGIH

# SAFETY DATA SHEET

## SOLID POWER (914100)

	Ceiling	2 mg/m <sup>3</sup>	NIOSH REL
	TWA	2 mg/m <sup>3</sup>	OSHA Z1

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

### Personal protective equipment

Eye protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Hand protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Skin protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Respiratory protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

### Product AT USE DILUTION

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

### Personal protective equipment

Eye protection : Wear eye protection/ face protection.

Hand protection : Wear the following personal protective equipment:  
Standard glove type.  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

	Product AS SOLD	Product AT USE DILUTION
Appearance	: Cast Solid	liquid
Color	: opaque, off-white	colorless
Odor	: slight	odorless
pH	: 12.0 - 13.0, 1 %	11.2 - 11.7
Flash point	: Not applicable, Does not sustain combustion.	
Odor Threshold	: No data available	
Melting point/freezing point	: No data available	

## SAFETY DATA SHEET

### SOLID POWER (914100)

Initial boiling point and boiling range	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: No data available
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Molecular weight	: No data available
VOC	: No data available

### SECTION 10. STABILITY AND REACTIVITY

#### Product AS SOLD

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: None known.
Incompatible materials	: Metals Acids Organic materials
Hazardous decomposition products	: Decomposition products may include the following materials: Carbon oxides Nitrogen oxides (NOx) Sulfur oxides Oxides of phosphorus

### SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Eye contact, Skin contact

#### Potential Health Effects

#### Product AS SOLD

Eyes : Causes serious eye damage.

## SAFETY DATA SHEET

### SOLID POWER (914100)

Skin : Causes severe skin burns.  
Ingestion : Causes digestive tract burns.  
Inhalation : May cause nose, throat, and lung irritation.  
Chronic Exposure : Health injuries are not known or expected under normal use.

#### Product AT USE DILUTION

Eyes : Causes serious eye damage.  
Skin : Causes severe skin burns.  
Ingestion : Causes digestive tract burns.  
Inhalation : May cause nose, throat, and lung irritation.  
Chronic Exposure : Health injuries are not known or expected under normal use.

#### Experience with human exposure

##### Product AS SOLD

Eye contact : Redness, Pain, Corrosion  
Skin contact : Redness, Pain, Corrosion  
Ingestion : Corrosion, Abdominal pain  
Inhalation : Respiratory irritation, Cough

#### Product AT USE DILUTION

Eye contact : Redness, Pain, Corrosion  
Skin contact : Redness, Pain, Corrosion  
Ingestion : Corrosion, Abdominal pain  
Inhalation : Respiratory irritation, Cough

#### Toxicity

##### Product AS SOLD

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Acute inhalation toxicity : 4 h Acute toxicity estimate : > 10 mg/l  
Acute dermal toxicity : No data available  
Skin corrosion/irritation : No data available  
Serious eye damage/eye irritation : No data available  
Respiratory or skin sensitization : No data available  
Carcinogenicity : No data available  
Reproductive effects : No data available  
Germ cell mutagenicity : No data available  
Teratogenicity : No data available

## SAFETY DATA SHEET

### SOLID POWER (914100)

STOT-single exposure : No data available  
STOT-repeated exposure : No data available  
Aspiration toxicity : No data available

### SECTION 12. ECOLOGICAL INFORMATION

#### Product AS SOLD Ecotoxicity

Environmental Effects : Harmful to aquatic life.

#### Product

Toxicity to fish : No data available  
Toxicity to daphnia and other aquatic invertebrates : No data available  
Toxicity to algae : No data available

#### Ingredients

Toxicity to fish : oxirane, methyl-, polymer with oxirane  
96 h LC50 Fish: > 100 mg/l

#### Ingredients

Toxicity to daphnia and other aquatic invertebrates : sodium hydroxide  
48 h EC50: 40 mg/l  
  
Sodium Carbonate(soda)  
48 h EC50 Daphnia : 200 mg/l

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

No data available

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Product AS SOLD

Disposal methods : The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

# SAFETY DATA SHEET

## SOLID POWER (914100)

RCRA - Resource Conservation and Recovery Authorization Act Hazardous waste : D002 (Corrosive)

### Product AT USE DILUTION

Disposal methods : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

## SECTION 14. TRANSPORT INFORMATION

### Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

### Land transport (DOT)

UN number : 1759  
Description of the goods : Corrosive solids, n.o.s. (sodium hydroxide)  
Class : 8  
Packing group : III  
Environmentally hazardous : no

### Sea transport (IMDG/IMO)

UN number : 1759  
Description of the goods : CORROSIVE SOLID, N.O.S. (sodium hydroxide)  
Class : 8  
Packing group : III  
Marine pollutant : no

### Product AT USE DILUTION

Not intended for transport.

## SECTION 15. REGULATORY INFORMATION

### Product AS SOLD

### EPCRA - Emergency Planning and Community Right-to-Know

### CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium hydroxide	1310-73-2	1000	1541

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

# SAFETY DATA SHEET

## SOLID POWER (914100)

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### California Prop 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

#### United States TSCA Inventory :

On TSCA Inventory

#### Canadian Domestic Substances List (DSL) :

All components of this product are on the Canadian DSL.

#### Australia Inventory of Chemical Substances (AICS) :

not determined

#### New Zealand. Inventory of Chemical Substances :

not determined

#### Japan. ENCS - Existing and New Chemical Substances Inventory :

not determined

#### Japan. ISHL - Inventory of Chemical Substances (METI) :

not determined

#### Korea. Korean Existing Chemicals Inventory (KECI) :

On the inventory, or in compliance with the inventory

#### Philippines Inventory of Chemicals and Chemical Substances (PICCS) :

not determined


#### China. Inventory of Existing Chemical Substances in China (IECSC) :

not determined

## SECTION 16. OTHER INFORMATION

### Product AS SOLD

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>3</b>
<b>FLAMMABILITY</b>	<b>0</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>


0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

# SAFETY DATA SHEET

## SOLID POWER (914100)

### Product AT USE DILUTION

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>3</b>
<b>FLAMMABILITY</b>	<b>0</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

Issuing date : 01/21/2015  
Version : 1.0  
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.