

SmokeCheck 25S (Smoke Alarm Tester)

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 03/17/2015

Revision date: 03/17/2015

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : SmokeCheck 25S (Smoke Alarm Tester)
Product code : Not available.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Smoke Alarm Tester

1.3. Details of the supplier of the safety data sheet

HSI Fire and Safety Group, LLC
107 Garlisch Drive
Elk Grove Village, IL - U.S.A.
T +1 (847) 427-8340 - F +1 (847) 427-8343
tbarakat@homesafeguard.com

1.4. Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture


GHS-US classification

Flammable Aerosol 1
Gases Under Pressure - Liquefied Gas

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

2.3. Other hazards

No additional information available.

2.4. Unknown acute toxicity (GHS US)

2 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable.

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Isobutane	(CAS No) 75-28-5	40 - 70	Flam. Gas 1 Liquefied gas
Propane	(CAS No) 74-98-6	15 - 40	Flam. Gas 1 Liquefied gas
Siloxane	Proprietary	1 - 5	Skin Irrit. 2 Eye Irrit. 2A STOT SE 3
Butane	(CAS No) 106-97-8	0.5 - 1.5	Flam. Gas 1 Liquefied gas

* The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SmokeCheck 25S (Smoke Alarm Tester)

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a poison center or a doctor if you feel unwell.
- First-aid measures after skin contact : If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists. Thaw frosted parts with lukewarm water. Do not rub affected area.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention. Thaw frosted parts with lukewarm water. Do not rub affected area.
- First-aid measures after ingestion : Not a normal route of exposure. If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation. Vapors may cause drowsiness and dizziness. Intentional misuse of product by inhalation can result in asphyxiation or death.
- Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause frostbite.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. May cause frostbite.
- Symptoms/injuries after ingestion : Not a normal route of exposure. May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray, foam, dry chemical.
- Unsuitable extinguishing media : Do not use carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon, oxides of nitrogen, oxides of sulfur.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Methods for cleaning up : Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Container may explode if heated. Use only non-sparking tools. When using do not eat, drink or smoke.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

SmokeCheck 25S (Smoke Alarm Tester)

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Store in a well-ventilated place.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Isobutane (75-28-5)		
ACGIH	ACGIH STEL (ppm)	1000 ppm
OSHA	Not applicable	

Propane (74-98-6)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Siloxane (Proprietary)	
ACGIH	Not applicable
OSHA	Not applicable

Butane (106-97-8)		
ACGIH	ACGIH STEL (ppm)	1000 ppm
OSHA	Not applicable	

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear suitable gloves: Viton gloves. Heat insulating gloves.

Eye protection : Safety glasses or goggles are recommended when using product.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas/Pressurized Liquid

Appearance : No data available

Color : Colorless

Odor : Slight ether-like

Odor threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Relative evaporation rate (ether=1) : > 1

Melting point : < -75 °C (< -99 °F)

Freezing point : No data available

Boiling point : -32 - 0 °C (-25 - 32 °F)

Flash point : < -75 °C (< -99 °F)

Auto-ignition temperature : > 462 °C (> 863 °F)

SmokeCheck 25S (Smoke Alarm Tester)

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable
Vapor pressure	: 4.41 bar @ 21 °C (70 °F), 64 psig 11.8 bar @ 54 °C (129 °F), 178 psig
Relative vapor density	: 1.79 @ 21 °C (70 °F)
Relative density	: 0.538 g/ml @ 21 °C (70 °F)
Solubility	: Water: 0.008 % @ 21 °C (70 °F)
Partition coefficient: n-octanol/water	: 1.35
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: < 0.6 cP @ 21 °C (70 °F)
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1.9 - 8.4 vol % @ 25 °C (77 °F)

9.2. Other information

VOC content : < 99 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Incompatible materials. Sources of ignition. Direct sunlight. Moisture.

10.5. Incompatible materials

Acids. Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, oxides of nitrogen, oxides of sulfur.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified.

SmokeCheck 25S (Smoke Alarm Tester)	
LD50 oral rat	No data available
LD50 dermal rabbit	No data available
LC50 inhalation rat	> 5 mg/l/4h
Isobutane (75-28-5)	
LC50 inhalation rat	658 mg/l/4h
Propane (74-98-6)	
LC50 inhalation rat	658 mg/l/4h
Butane (106-97-8)	
LC50 inhalation rat	658 mg/l/4h

Skin corrosion/irritation	: Based on available data, the classification criteria are not met.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.

SmokeCheck 25S (Smoke Alarm Tester)

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation. Vapors may cause drowsiness and dizziness. Intentional misuse of product by inhalation can result in asphyxiation or death.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause frostbite.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. May cause frostbite.
Symptoms/injuries after ingestion	: Not a normal route of exposure. May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

SmokeCheck 25S (Smoke Alarm Tester)

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

SmokeCheck 25S (Smoke Alarm Tester)

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available.

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT

UN-No.(DOT)	: UN1950
Proper Shipping Name (DOT)	: Aerosols, flammable
Department of Transportation (DOT) Hazard Classes	: 2.1
Hazard labels (DOT)	:



Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

SmokeCheck 25S (Smoke Alarm Tester)

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

15.2. US State regulations

SmokeCheck 25S (Smoke Alarm Tester)

State or local regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16: Other information

Date of issue : 03/17/2015

Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.